Příloha C (informativní)– Příklady užití protokolu informačního managementu

Struktura přílohy C je shodná se strukturo položek protokolu informačního managementu a pro každou její část je uveden příklad nastavení a obsahové náplně.
Jako příklad je uvedena tabulka atributů zprávy (message):

Tabulka č.2 – Příklad nastavení hodnot ve struktuře protokolu pro přenos zpráv (tab. C.1 normy)

		Attributes of request messages	Attributes of response messages
Selection of communication system	**Responsiveness**	Within 30 seconds	Undefined
	Directionality	Interactive (ascending < descending)	Unidirectional
	Usage environment	Vehicle movement – speed	Vehicle movement – speed
	Service area	Discontinuous	Continuous
	Service time	Continuous	Continuous
	Bandwidth	Text data at about 10 kbps	Text and graphics data at about 100 kbps
	Connection cost	Undefined	Undefined
Application identifiers	**Message identifier**	Specification of emergency vehicle guidance request messages	Specification of emergency vehicle guidance response messages
	Message number	Specification of a sequential number	Specification of a sequential number
	Time of message transmission	Specification of time	Specification of time
Address	**Address of origin**	Compatible with Ipv6	Compatible with IPv6
	Address of destination	Compatible with Ipv6	Compatible with IPv6
Priority	**Interrupt handling**	High priority	High priority
	Queue control	Undefined	Undefined
Security	**Mutual authentication**	Undefined	Undefined
	Data authentication	Undefined	Undefined
	Concealment	Undefined	Undefined
Application execution	**Valid time**	Until time of information updating	Until time of information updating
	Time stamp	Undefined	Specification of time
	Target area	Spot	Interval

© Silmos, s.r.o. 2018 - 2025. *Pomůžeme Vám se zorientovat v oboru Dopravní telematiky a najít správnou normu.*